

Cleaning and Maintenance Information

KB577 Transition Strip

Data Sheet: Page 1 of 1 15.05.18

This leaflet has been compiled to help the user obtain optimum performance and satisfaction from their selected product:

Preventative Maintenance Programme

A regular scheduled maintenance programme should be employed to prevent the build up of dirt and grease, which will reduce the anti-slip properties of the profile and detract from the overall appearance of the product.

Daily Cleaning

Brush down the profiles using a soft bristled brush and remove dust particles from the insert by wiping with a damp cloth.

Twice Weekly or as Required

With clean, hand warm water, containing the correct dilution ratio of ph neutral cleaning solution apply a small amount to a wet green scotch pad and gently clean the surface of the profile in a left to right motion. During the clean, the water must be changed on a regular basis. Once the profile has been cleaned thoroughly rinse with fresh, clean water and dry with a dry lint free cloth.

In case of spillage the profile should not be used until completely dry.

NB. Under no circumstances should floor cleaners or sanitizers containing citrus based agents or hydrocarbons be used to clean any Gradus profile.

Aluminium Profile

Stubborn marks such as boot blacking may be removed from the aluminium profile by means of a green scotch pad and neutral detergent. Light surface scratches can be removed with careful use of fine wire wool and buffed with a soft cloth.