

### Gradus & NBS Specifications

---

#### Topguard Primary Barrier Matting

Data Sheet: Page 1 of 1 16.12.22

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Topguard is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

#### NBS Specification

##### N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

##### 300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

**Manufacturer:** Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: [www.gradus.com](http://www.gradus.com) Email: sales@gradus.com

**Reference:** Topguard Primary Barrier Matting

**Construction (select as required):** Closed or Open (5mm), Single or Double wipers, 12mm or 18mm height

**Linking strip material (select as required):** Aluminium or Brass (Brass 18mm only)

**Wiper colour (select as required):** Grey or Black

**Fixing:** recessed in matwell – as per manufacturers instructions

#### Gradus Detailed Specification

**Manufacturer:** Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: [www.gradus.com](http://www.gradus.com) Email: sales@gradus.com

**Reference:** Topguard Primary Barrier Matting

**Construction (select as required):** Closed or Open (5mm), Single or Double wipers, 12mm or 18mm height

**Linking strip material (select as required):** Aluminium or Brass (Brass 18mm only)

**Wiper colour (select as required):** Grey or Black

**Total height (select as required):** 12mm or 18mm

**Fixing:** recessed in matwell – as per manufacturers instructions

#### Installation accessories available:

**T Bar 12 / T Bar 18:** 12mm / 18mm Aluminium divider bar

**UMFA12 / UMFA18 / UMFA25:** 12mm / 18mm / 25mm aluminium matwell frame

**FRB026:** 20mm brass matwell frame

#### Description

Topguard is constructed from rubber wipers and scraper linking strips which are held together with galvanised steel wires. The rubber wipers are interwoven with nylon fibres in a choice of grey or black. The scraper linking strips are available in either aluminium or brass. When installed as a true rectangle or a square Topguard can be reversed to extend the product's life. For a complete matting solution Topguard can also be used with Boulevard secondary barrier matting.