

Data Sheet: Page 1 of 2 AH/DW 02.10.23

NBS & Gradus Specification

BRXT81R - XT Bronze Stair Edging

Gradus is a member of NBS Source, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for BRXT81R is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/750/550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ **Tel:** 01625 428922 **Website:** www.gradus.com **Email:** sales@gradus.com

Reference: ▶BRXT81R with Metal Castellated insert

Profile Material: Bronze profile available in Polished Bronze or Satin Bronze finish

Insert Material: Metal Castellated (Bronze & Aluminium finish options available - see below)

Insert Finishes (select as required): Bronze inserts available in Polished Bronze (LRV: 66.86), Satin Bronze (LRV: 59.60) and Aluminium inserts available in Aluminium Mill finish (LRV: 74.21), Black Anodised (LRV: 4.35), Antique Brass (LRV: 9.78), Antique Bronze (LRV: 7.55), Brushed Stainless Steel (LRV: 48.85), Polished Chrome (LRV: 58.17),

Satin Chrome (LRV: 50.73)

Fixing: Gradus Grip GG290 (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per

manufacturer's instructions

Reference: ▶BRXT81R with Xtra-grip insert

Profile Material: Bronze profile available in Polished Bronze or Satin Bronze finish

Insert Material: Pvc insert

Insert Colour (select as required): Onyx (LRV: 4.52), Neptune (LRV: 5.03), Claret (LRV: 5.70), Umber (LRV: 5.71),

Forest (LRV: 6.69), Aegean (LRV: 7.02), Baltic (LRV: 8.00), Graphite (LRV: 12.56), Chestnut (LRV: 15.36), Quarry (LRV: 24.71), Sepia (LRV: 27.71), Tuscan (LRV: 34.86), Concrete (LRV: 37.44), Ochre (LRV: 49.97),

Surf (LRV: 43.58), Pumice (LRV: 46.83), Bamboo (LRV: 45.84), Frost (LRV: 66.51)

Fixing: Gradus Grip GG290 (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per

manufacturer's instructions

Or

Reference: ▶BRXT81R with Interior Standard Finish insert

Profile Material: Bronze profile available in Polished Bronze or Satin Bronze finish

Insert Material: Pvc insert

Insert Colour (select as required): Jet (LRV: 4.56), Ink (LRV: 4.96), Burgundy (LRV: 5.70), Coffee (LRV: 6.05),

Evergreen (LRV: 6.69), Teal (LRV: 7.02), Ocean (LRV: 8.00), Lead (LRV: 12.77), Spice (LRV: 15.35), Steel (LRV: 26.99), Bronze (LRV: 27.71), Linen (LRV: 38.59), Glacier (LRV: 42.09), Canvas (LRV: 53.27), Clay (LRV: 47.97), Sky (LRV: 52.63),

Jade (LRV: 53.98), Wisp (LRV: 58.17), Buttercup (LRV: 55.54), Snowdrift (LRV: 83.77)

Fixing: Gradus Grip GG290 (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per

manufacturer's instructions

▶ New – stock of BRXT81R and all associated finishes and inserts available January 2024



Data Sheet: Page 2 of 2 AH/DW 02.10.23

NBS & Gradus Specification

BRXT81R – XT Bronze Stair Edging

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ **Tel:** 01625 428922 **Website:** www.gradus.com **Email:** sales@gradus.com

Reference: ▶BRXT81R Gauge: Ramp back Tread Dimension: 70mm Riser Dimension: 40mm

Channel: Bronze channel with single, slip-resistant Pvc or Metal Castellated insert

Profile Finishes: Polished Bronze or Satin Bronze

Profile Shape: Bullnose

Insert Type & Colour (select as required):

Metal Castellated insert with low risk of slip in both wet and dry interior conditions (PTV >36 in wet and dry conditions) in colour: Polished Bronze (LRV: 66.86), Satin Bronze (LRV: 59.60) and Aluminium inserts available in Aluminium Mill finish (LRV: 74.21), Black Anodised (LRV: 4.35), Antique Brass (LRV: 9.78), Antique Bronze (LRV: 7.55), Brushed Stainless Steel (LRV: 48.85), Polished Chrome (LRV: 58.17), Satin Chrome (LRV: 50.73)

Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV >36 in wet and dry conditions) in colour: Onyx (LRV: 4.52), Neptune (LRV: 5.03), Claret (LRV: 5.70), Umber (LRV: 5.71), Forest (LRV: 6.69), Aegean (LRV: 7.02), Baltic (LRV: 8.00), Graphite (LRV: 12.56), Chestnut (LRV: 15.36), Quarry (LRV: 24.71), Sepia (LRV: 27.71), Tuscan (LRV: 34.86), Concrete (LRV: 37.44), Ochre (LRV: 49.97), Surf (LRV: 43.58), Pumice (LRV: 46.83), Bamboo (LRV: 45.84), Frost (LRV: 66.51)

Or

Interior Standard Finish insert with low risk of slip in interior dry conditions (PTV >36) in colour: Jet (LRV: 4.56), Ink (LRV: 4.96), Burgundy (LRV: 5.70), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Teal (LRV: 7.02), Ocean (LRV: 8.00), Lead (LRV: 12.77), Spice (LRV: 15.35), Steel (LRV: 26.99), Bronze (LRV: 27.71), Linen (LRV: 38.59), Glacier (LRV: 42.09), Canvas (LRV: 53.27), Clay (LRV: 47.97), Sky (LRV: 52.63), Jade (LRV: 53.98), Wisp (LRV: 58.17), Buttercup (LRV: 55.54), Snowdrift (LRV: 83.77)

Recommended Side Trim(s): Not applicable

Fixing: Gradus Grip GG290 (adhesive only) – as per manufacturer's instructions OR Mechanical & adhesive fix – as per manufacturer's instructions

▶ New – stock of BRXT81R and all associated finishes and inserts available January 2024

Description

XT range

A range of bronze stair edgings incorporating an extended insert that continues around the leading edge of the profile to ensure that contact is always made with the slip resistant element of the stair edging in line with the latest research undertaken by BRE (Information Paper 15/03). Insert is mechanically locked in place to provide added resistance to cleaning regimes.