

Lafite

Product information:

The Lafite and Lafite Stripes ranges offer durability, functionality and design. The ranges can be used alone or can work together to create interesting and unique floor schemes. Lafite and Lafite Stripes are suitable for a wide variety of commercial and educational environments.



Warranties:

10 year wear warranty
 10 year anti-static warranty
 Full warranty details available on request



Environmental Profiles
 ENP 399dv & 399dw

BRE Global (BREEAM):

'A+' Education (tile)
 'A+' Healthcare (tile)
 'A+' Retail replacement by fashion (tile)

Specification:

Product Form	Tile
Product Dimensions	500mm x 500mm
Product Construction	Tufted Loop Pile
Surface Yarn	100% Aquafil Solution Dyed Nylon
Total Weight	4375 g/m ²
Tufted Pile Weight	500 g/m ²
Gauge	39.4 per dm
Stitches	43.3 per dm
Primary Backing	Non-woven
Secondary Backing	Bitumen
Total Carpet Thickness	6.8mm

Performance Specification

Classification BSEN 1307	Wear Class 33
Castor Chair BSEN 985 Test A	Pass
Static Electricity ISO 6356	<2kV

Flammability

BSEN 13501-1	Class Bfl-s1
--------------------	--------------


For recommended adhesives contact Technical Services on 01625 428922.



Lafite




Broadloom



Quarter Turn

Lafite Stripes



Must be laid Quarter Turn



ISO 9001 : FM 10763
 ISO 14001 : EMS 59511



BS OHSAS 18001
 IV 18/18493

15834

GRADUS

Gradus Carpets Park Green Macclesfield Cheshire SK11 7LZ England UK Tel: 01625 859000 Fax: 01625 850352

For enquiries outside the UK and Eire contact Gradus International on +44 (0)1625 613780

www.gradusworld.com