

NBS & Gradus Specification

ELAF5150

Data Sheet: Page 1 of 2 AH 06/07/18

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for ELAF5150 shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

M50 RUBBER/PLASTICS/CORK/LINO/CARPET TILING/SHEETING

75/ 750/ 550 STAIR NOSINGS AND TRIMS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 **Fax:** 01625 433939

Website: www.gradus.com **Email:** sales@gradus.com

Reference: ELAF5150 with Xtra-grip Insert

Material: Aluminium channel with PVC insert

Colour: Onyx (LRV: 4.52), Quarry (LRV: 24.71), Graphite (LRV: 12.56), Ochre (LRV: 49.97) (select as required)

Fixing: Mechanical (screw) and adhesive fix – as per manufacturers instructions

or

Reference: ELAF5150 with Interior Insert

Material: Aluminium channel with PVC insert

Colour: Interior Insert: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Cloud (LRV: 28.57), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Linen (LRV: 38.59), Midnight (LRV: 6.56), Ocean (LRV: 8.00), Poppy (LRV: 10.39), Snowdrift (LRV: 83.77), Steel (LRV: 26.99), (select as required)

Fixing: Mechanical (screw) and adhesive fix – as per manufacturers instructions

LED Options: Available with Continuity (continuous light effect) or Interlok Advance (pinpoint light effect) in 5 LED colours – Blue, Green, Amber, Red and White

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 **Fax:** 01625 433939

Website: www.gradus.com **Email:** sales@gradus.com

Reference: ELAF5150

Gauge: 5mm

Tread Dimension: 76mm

Riser Dimension: 25mm

Channel: Mill finish aluminium channel with PVC insert.

Profile Shape: For Square Steps with Angled Face

Insert Type & Colour (select as required):

Xtra-grip insert with low risk of slip in both wet and dry interior conditions (PTV 64 (wet conditions) PTV 70 (dry conditions)) in colour: Onyx (LRV: 4.52), Quarry (LRV: 24.71), Graphite (LRV: 12.56), Ochre (LRV: 49.97)

or

Interior Insert - with low risk of slip in interior dry conditions (PTV 68). Interior Insert in colour: Burgundy (LRV: 5.70), Buttercup (LRV: 55.54), Canvas (LRV: 53.27), Cloud (LRV: 28.57), Coffee (LRV: 6.05), Evergreen (LRV: 6.69), Glacier (LRV: 42.09), Ink (LRV: 4.96), Jet (LRV: 4.56), Lead (LRV: 12.77), Linen (LRV: 38.59), Midnight (LRV: 6.56), Ocean (LRV: 8.00), Poppy (LRV: 10.39), Snowdrift (LRV: 83.77), Steel (LRV: 26.99)

LED Options: Available with Continuity (continuous light effect) or Interlok Advance (pinpoint light effect) in 5 LED colours – Blue, Green, Amber, Red and White

Accessories: LR1238 square tube: EC5150RHI End Cap with Row Indicator, EC5150RH End Cap

Fixing: Mechanical (screw) and adhesive fix – as per manufacturers instructions

Description

Gradus offers a range of safety and decorative lighting profiles for stairs that have been designed specifically to suit interior environments such as auditoria, where light is required for safety but should not detract from the primary function of the installation. By utilising LED technology, the system offers an extra low voltage alternative to mains voltage lighting. The step systems are also modular in design, making them quick and easy to install.

Two lighting options are available with either the Interlok Advance LED system that produces a pinpoint lighting effect or with Continuity LED system that produces a continuous lighting effect. Both systems can be used in the range of stair edging profiles as well as floor trims to produce a range of lighting effects.