

Gradus & NBS Specifications

Boulevard 5000 Secondary Barrier Matting

Data Sheet: Page 1 of 2 19.01.22

Gradus is a member of NBS Plus, providing a comprehensive library of pre-written specifications supported by guidance notes. The NBS specification for Boulevard 5000 is shown below, plus a detailed Gradus specification and profile description to ensure the correct specification is maintained. For further information on NBS contact NBS Services on 0191 232 9594.

NBS Specification

N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

300 ENTRANCE MATTING / 40 MISCELLANEOUS FITTINGS

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Boulevard 5000 Secondary Barrier Matting

Colour (select as required): Corncrake (LRV: 9.52), Cuckoo (LRV: 5.63), Falcon (LRV: 5.11) Jackdaw (LRV: 1.73), Kestrel (LRV: 5.42), Moorhen (LRV: 2.98), Redpoll (LRV: 4.14), Shelduck (LRV: 5.20), Swallow (LRV: 2.08)

Fixing: adhesive – as per manufacturers instructions

Gradus Detailed Specification

Manufacturer: Gradus Accessories, Park Green, Macclesfield, Cheshire, SK11 7LZ.

Tel: 01625 428922 Fax: 01625 433939

Website: www.gradus.com Email: sales@gradus.com

Reference: Boulevard 5000 Secondary Barrier Matting

Product construction: Tufted Cut Pile

Surface yarn: ECONYL® Regenerated Solution Dyed Nylon

Dimensions / backing: Broadloom: Roll 2m x 25m, pvc, non-woven primary backing, Tile: 500mm x 500mm, bitumen, non-woven primary backing

Pile height: 5mm nominal

Tufted pile weight: 800g/m²

Total carpet thickness: Broadloom: 7.5mm nominal, Tile: 8mm nominal

Total pile weight: Broadloom: 800g/m, Tile: 800g/m²

Colour (select as required): Corncrake (LRV: 9.52), Cuckoo (LRV: 5.63), Falcon (LRV: 5.11) Jackdaw (LRV: 1.73), Kestrel (LRV: 5.42), Moorhen (LRV: 2.98), Redpoll (LRV: 4.14), Shelduck (LRV: 5.20), Swallow (LRV: 2.08)

Performance Specification

Classification – BS EN 1307: Class 3

Static Electricity - ISO 6356: <2kV

Flammability

Fire rating – BS EN 13501-1: Class Bfl-s1

Warranty: 5 years wear warranty

Fixing: Recommended adhesive. F. Ball & Co. 01538 361633. Product: F45

Description

Boulevard 5000 is a traditional style secondary barrier carpet that incorporates a light scraper fibre for use in any area of a building prone to soil and moisture damage. Ideal for use as a classic style barrier carpet, it can also form a border surrounding other Gradus secondary barrier products, providing more design options in areas such as canteens, receptions and corridors. In some situations, Boulevard 5000 can be used as stand alone matting in entrances and access points. Boulevard 5000 is designed to complement Esplanade 5000 primary barrier matting and Access 5000 and Mat-in-a-Box 5000 hybrid barrier matting.

Gradus Limited Park Green Macclesfield Cheshire SK11 7LZ England UK Tel: 01625 428922 Fax: 01625 433949

For enquiries outside the UK and Eire contact Gradus International on +44 (0)1625 613780

www.gradus.com

